

TOWN OF HARWICH

DIVISION OF HIGHWAYS & MAINTENANCE P.O. Box 1543 Harwich, MA 02645 Telephone: (508) 430-7555 Fax: (508) 430-7598

ROAD CUT/EXCAVATION PERMIT APPLICATION

GENERAL INSTRUCTIONS:

- 1. Please complete application
- 2. Provide sketch or site plan with application
- 3. Return completed application to Highway Department

Applicant:			Telephone:
Address:			-
Construction Address:			
Contractor Name:			
Contractor Address:			
Contact Person:			Telephone:
Type of Activity:			-
☐ Gas Installation/Repair☐ Other: (please explain)	☐ Water Service	Installation/Repair	☐ Drainage Installation/Repair
Area to be excavated:	☐ Sidewalk	□ Shoulder	☐ Travel Lane
Dimensions of excavation:	Length	Width	Depth
Work Dates: Starting		Completion_	***************************************
The applicant acknowledges the document, and agrees to abide	nat he/she has read by these and any o	the above and specific ther rules or regulation	ations on the reverse side of this as of the Town of Harwich.
Signature of Applicant			Date
Highway Department Authoriz	zation		Date

Copies:

White: Highway Department

Yellow: Applicant

TRENCHES:

- 1. All trenches opened within a town layout will be opened wide enough to allow a mechanical tamper to compact material in layers no greater than one (1) foot. Each layer will be compacted to a density equal to that of adjacent original materials.
- 2. After compaction of the sub-base three (3) inches of T-base material will be layered and compacted to the same density as the product below.
- 3. The remaining three (3) inches will be of bituminous concrete applied in 1 ½ inch lifts of no less than a modified top grade product, which will be compacted to that equal with the existing road structure.
- 4. Whether or not this excavation needs to be infrared patched will be determined upon completion by the Director of Highways or his/her designee.

SHOULDERS:

1. All road shoulders will be compacted as to a density equal to that of the adjacent original material and rebuilt to the original grade with no less than three (3) inches of loam, seeded, rolled and fertilized.

SIDEWALKS:

1. All sidewalk excavations will be compacted to a density equal to the adjacent original material and will be returned to its original condition (i.e.: bituminous concrete, concrete, cement, brick, etc.)

WARRANTEE:

- 1. The repairs shall be warranted for a period of one (1) year from date of completion
- 2. The contractor will perform any repairs to the satisfaction of the Director of Highways or his designee.
- 3. All required repairs will be at no cost to the Town and will be the responsibility of the contractor.

GENERAL INFORMATION

- 1. The tree warden **must** be notified if the proposed work requires the removal or trimming of a tree if any part thereof is within the public way layout.
- 2. CALL DIG SAFE 1-888-344-7233